

Energysaver™ Centramatic Duo

Centrifugal fan



Our new Energysaver™ Centramatic Duo, one size, centrifugal fan is designed for all kitchen and bathroom applications. The standard 100mm unit features an offset mounting spigot that simplifies positioning and installation procedures.

The Centramatic Duo offers three levels of ventilation:




- Constant trickle
- Humidistat control
- Pull cord boost

Airtech Energysaver™ Cowls that further increase energy efficiency by up to 20% are supplied with all Centramatic Duo fans. The Cowls alleviate 'blow back', increase extractor fan efficiency and reduce energy consumption - all of which contribute to a reduction in the carbon footprint.

Integral sensors and switches ensure the units can be controlled wherever they are located.

Benefits

- Suitable for kitchens and bathrooms
- Integral jumper easily permits either kitchen or bathroom installations
- Contamination proof humidistat with lifetime guarantee provides accurate humidity control
- Humidistat set point can be changed
- 100mm spigot with offset makes installation easier and quicker, especially in corner locations
- Constant trickle ventilation meets Building Regulations
- Humidity boost increases ventilation when humidity levels rise
- Pull cord boost increases extract when required to remove odours
- Stores up to five weeks of humidity data and records any power disconnections
- Complies with Building Regulations Part L
- Up to 5 year warranty depending on motor type



ORDER CODES (For data logging facility please add L to the order code)

DUO/AC 240v	Constant trickle fan with integral humidistat sensor and pull cord boost.	DUO/ESPC 12v	Constant trickle fan with pull cord boost
DUO/PC 240v	Constant trickle fan with pull cord boost	DUO/ES/RPS 12v	Constant trickle fan with integral humidistat, pull cord boost and remote power supply
DUO/ES 12v	Constant trickle fan with integral humidistat and pull cord boost	DUO/PC/RPS 12v	Constant trickle fan with pull cord boost and remote power supply

TECHNICAL DATA

Dimensions:	Duo AC100	A 230mm	B 230mm	C 104mm	D 122mm	E 18mm	F 97mm
	Duo DC100 Energysaver™	A 230mm	B 230mm	C 104mm	D 122mm	E 18mm	F 97mm
Hole dimensions	Duo AC100	100mm dia.		Duo DC100 Energysaver™	100mm dia.		
Insulation	Double insulated			Double insulated			
Voltage	240			12			
Power	38 watts			10 watts			
Extract capacity cu m/hr	90			90			
Trickle (Kitchen/Bathroom)	13/ 8			13 / 8			
Humidistat (Kitchen/Bathroom)	28 / 10			28 / 10			
Boost (Kitchen/Bathroom)	49 / 25			49 / 25			
Pressure mm H2O	11			11			
dB(A)	45			45			



HEAD OFFICE
 Stathe Road
 Burrowbridge
 Somerset, TA7 0RY
 Tel: 01823 690292 Fax: 01823 690291
 Email: info@airtechaunton.co.uk
 www.airtechenvironmental.co.uk

LONDON & SOUTH EAST REGION
 Suite 2, First Floor, Cadogan House,
 36 Central Avenue, West Molesey,
 Surrey, KT8 2QZ
 Tel: 020 8941 8722 Fax: 020 8941 9623
 Email: info@airtechlondon.co.uk
 www.airtechenvironmental.co.uk

SOUTH WEST REGION
 Unit 2 Halwin Industrial Estate
 Porkellis, Helston
 Cornwall, TR13 0LA
 Tel: 01326 341423 Fax: 01326 341467
 Email: info@airtechaunton.co.uk
 www.airtechenvironmental.co.uk

