

Duo Compact Energysaver™

Fan for kitchens and bathrooms



Our all new Duo Compact twin fan has been designed for easy fitting into kitchens and bathrooms. Featuring modern styling, the latest electronics and unique twin fan construction, it delivers enhanced energy efficient performance and reliability coupled with dramatically reduced power consumption, noise level and maintenance.

The Duo Compact offers two levels of ventilation:

- Constant trickle
- Pull cord boost



Duo /H and G models also feature humidistat controls.

These options combine to optimise air quality and minimise the impact of moisture in most household environments.

To maximise energy efficiency Airtech Energysaver™ Cowlings are supplied as standard. These innovative products increase energy efficiency by up to 20% and boost extractor fan efficiency to reduce energy consumption – all of which contribute to a reduction in carbon footprint.

Benefits

- Fit and forget
- Suitable for kitchens and bathrooms
- Stylish design
- Quiet operation – over 30% quieter than previous models
- Easy to use
- Three modes provide constant air quality and humidity control
- Low running costs – equal to two 12W energy saving (60W equivalent) light bulbs on for four hours every day per year
- 100mm standard size
- Wall or window fitting
- Energy saving DC motors
- Twin fan construction ensures powerful and reliable operation
- Filter-less design minimises maintenance
- Remote humidistat can be located in best position
- Constant trickle ventilation meets building regulations
- Humidity boost increases ventilation when humidity levels rise
- Pull cord boost increases extract when required to remove odours
- Can be supplied with data capture software
- 5 year warranty



ORDER CODES

DUO	Constant trickle / pull cord boost / wall fitting
DUO/H	Constant trickle / pull cord boost / humidity boost / wall fitting
DUO/G	Constant trickle / pull cord boost / window fitting
DUO/H/G	Constant trickle / pull cord boost / humidity boost / window fitting

For data logging add 'd' to any code

TECHNICAL DATA

Dimensions	A	B	C	D	E	F	G
Duo Compact ES	164mm	154mm	32mm	62mm	30mm	98mm	39mm
Hole Dimension	100 mm dia.						
Insulation	Double insulated						
Motor output	12V DC						
Motor power consumption	2.0W						
Extract capacity	108m ³ /h (64 cfm)						
Trickle	12 litres/second						
Boost	30 litres/second						
Pressure	70Pa						
Noise levels							
Trickle	32.2dB(A)						
Boost	45 dB(A)						



HEAD OFFICE

Stathe Road
Burrowbridge
Somerset, TA7 0RY
Tel: 01823 690292 Fax: 01823 690291
Email: info@airtechaunton.co.uk
www.airtechenvironmental.co.uk

LONDON & SOUTH EAST REGION

Suite 2, First Floor, Cadogan House,
36 Central Avenue, West Molesey,
Surrey, KT8 2QZ
Tel: 020 8941 8722 Fax: 020 8941 9623
Email: info@airtechlondon.co.uk
www.airtechenvironmental.co.uk

SOUTH WEST REGION

Unit 2 Halwin Industrial Estate
Porkellis, Helston
Cornwall, TR13 0LA
Tel: 01326 341423 Fax: 01326 341467
Email: info@airtechaunton.co.uk
www.airtechenvironmental.co.uk